

## TYRES

Product group	Tyres
Item number	15212758
Valid tyre size	710 / 45 - 26.5
LI / SI / PR	175 A2 / 168 A8, 20 PR
TL/TT	TT
Brand	Alliance
Tread pattern	Forestar 644 III



## Notes and features

- The Alliance Forestar 644 III is a versatile forestry tyre for different applications.
- Its dual lug angles provide excellent grip and traction.
- Thanks to the improved steel belt casing and the special hexagonal bead technology, the tyre offers outstanding puncture resistance, stability, high loading capacities and low slip.
- The special shoulder design and curb-rib design of the sidewall provide stiffness and protection from side impacts.
- The large contact area ensures low soil compaction.
- The angled lugs form wide blocks in the centre of the tread to ensure stability and ride comfort.

**Technical Informations**

Item number	15212758
EAN	8903635022930
Valid tyre size	710 / 45 - 26.5
LI / SI / PR	175 A2 / 168 A8, 20 PR
TL/TT	TT
Brand	Alliance
Tread pattern	Forestar 644 III
TRA Code	LS-2
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	218,00
Recommended rim size	AG24.00
Maximum air pressure [bar].	5,50
Section width (mm)	710
Outer diameter of tyre [mm].	1340
Stat. radius (SLR) [mm]	628
Rolling circumference [mm].	4098
Tread depth (mm)	51,0
Number of lugs	16x2
Tyre capacity 75% [ltr.]	303.65
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
175 A2	6900	10		5,50	
168 A8	5600	40		5,50	