

## TYRES

Product group	Tyres
Item number	15212764
Valid tyre size	800 / 40 - 26.5
LI / SI / PR	177 A2 / 170 A8, 20 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Forestar 344 ELIT



## Notes and features

- The Alliance 344 Forestar Elit is the first and, until now, only low-pressure tyre for forestry use.
- The innovative ELIT technology (Engineered Low Inflation Tyre) enables the same loading capacity at 50% reduced inflation pressure compared with a standard forestry tyre.
- Its large footprint, enlarged by 26%, provides high traction and optimum soil protection.
- Additionally, the special construction offers excellent sidewall stability.
- Due to the steel belt-reinforced casing and the special forestry rubber compound, the tyre is protected against punctures and premature wear ensuring a long service life.
- The tractor pattern provides good grip and self-cleaning on all surfaces.
- The close spacing between the lugs in the tread centre leads to reduced rolling resistance when driving on hard surfaces.

## Technical Informations

Item number	15212764
EAN	7291050062138
Valid tyre size	800 / 40 - 26.5
LI / SI / PR	177 A2 / 170 A8, 20 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Forestar 344 ELIT
TRA Code	HF-2
Carcass properties	Low Pressure
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	231,00
Recommended rim size	28.00
Maximum air pressure [bar].	2,50
Section width (mm)	800
Outer diameter of tyre [mm].	1340
Stat. radius (SLR) [mm]	600
Rolling circumference [mm].	3993
Tread depth (mm)	50,8
Number of lugs	16x2
Tyre capacity 75% [ltr.]	384
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
177 A2	7300	10		2,50	
170 A8	6000	40		2,50	