

TYRES

Product group	Tyres
Item number	15212841
Valid tyre size	750 / 55 - 26.5
LI / SI / PR	184 A2 / 177 A8, 20 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Forestar 344 ELIT



Notes and features

- The Alliance 344 Forestar Elit is the first and, until now, only low-pressure tyre for forestry use.
- The innovative ELIT technology (Engineered Low Inflation Tyre) enables the same loading capacity at 50% reduced inflation pressure compared with a standard forestry tyre.
- Its large footprint, enlarged by 26%, provides high traction and optimum soil protection.
- Additionally, the special construction offers excellent sidewall stability.
- Due to the steel belt-reinforced casing and the special forestry rubber compound, the tyre is protected against punctures and premature wear ensuring a long service life.
- The tractor pattern provides good grip and self-cleaning on all surfaces.
- The close spacing between the lugs in the tread centre leads to reduced rolling resistance when driving on hard surfaces.

Technical Informations

Item number	15212841
EAN	7291050084574
Valid tyre size	750 / 55 - 26.5
LI / SI / PR	184 A2 / 177 A8, 20 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Forestar 344 ELIT
TRA Code	HF-2
Carcass properties	Low Pressure
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	264,00
Recommended rim size	AG24.00
Maximum air pressure [bar].	2,50
Section width (mm)	750
Outer diameter of tyre [mm].	1485
Stat. radius (SLR) [mm]	664
Rolling circumference [mm].	4436
Tread depth (mm)	51,5
Number of lugs	16x2
Tyre capacity 75% [ltr.]	507
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
184 A2	9000	10		2,50	
177 A8	7300	40		2,50	