

## **TYRES**

Product group	Tyres	
Item number	15212843	
Valid tyre size	750 / 55 - 26.5	
LI / SI / PR	189 A2 / 182 A8, 24 PR	
TL/TT	тт	
Brand	Alliance	
Tread pattern	Forestar 644 III	





## Notes and features

- The Alliance Forestar 644 III is a versatile forestry tyre for different applications.
- Its dual lug angles provide excellent grip and traction.
- Thanks to the improved steel belt casing and the special hexagonal bead technology, the tyre offers outstanding puncture resistance, stability, high loading capacities and low slip.
- The special shoulder design and curb-rib design of the sidewall provide stiffness and protection from side impacts.
- The large contact area ensures low soil compaction.
- The angled lugs form wide blocks in the centre of the tread to ensure stability and ride comfort.



## **Technical Informations**

Item number	15212843
EAN	8903635022947
Valid tyre size	750 / 55 - 26.5
LI / SI / PR	189 A2 / 182 A8, 24 PR
TL/TT	тт
Brand	Alliance
Tread pattern	Forestar 644 III
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	270,00
Recommended rim size	24.00
Maximum air pressure [bar].	6,00
Section width (mm)	750
Outer diameter of tyre [mm].	1490
Stat. radius (SLR) [mm]	683
Rolling circumference [mm].	4467
Tread depth (mm)	51,0
Number of lugs	17x2
Tyre capacity 75% [ltr.]	454.43
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
189 A2	10300	10		6,00	
182 A8	8500	40		6,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.