

TYRES

Product group	Tyres	
Item number	15212848	
Valid tyre size	750 / 55 - 26.5	
LI / SI / PR	184 A2 / 177 A8, 20 PR	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Forestar 343	





Notes and features

- The Alliance Forestar 343 is particularly suitable for harvesters and transport vehicles in forestry applications.
- Its wide, robust and low-angled lugs provide excellent grip in a wide range of forestry terrains.
- Due to the strong nylon casing with steel breakers, extrasturdy rubber compound, thick undertread gauge and reinforced sidewalls, the tyre is particularly robust.
- The Alliance Forestar 343 can be used on CTL machines.



Technical Informations

Item number	15212848
EAN	7291050058025
Valid tyre size	750 / 55 - 26.5
LI / SI / PR	184 A2 / 177 A8, 20 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Forestar 343
TRA Code	LS-2
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	256,64
Recommended rim size	24.00
Maximum air pressure [bar].	5,00
Section width (mm)	750
Outer diameter of tyre [mm].	1485
Stat. radius (SLR) [mm]	690
Rolling circumference [mm].	4536
Tread depth (mm)	29,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
184 A2	9000	10		5,00	
177 A8	7300	40		5,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.