

TYRES

Product group	Tyres
Item number	15212849
Valid tyre size	750 / 55 - 26.5
LI / SI / PR	184 A2 / 177 A8, 20 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Forestar 344



Notes and features

- The Alliance Forestar 344 is a powerful forestry tyre for CTL machines.
- The steel-reinforced nylon casing, the special rubber compound, as well as the reinforced sidewalls, protect the tyre against punctures.
- The traction tread pattern with low-angled lugs provides excellent grip and good self-cleaning thanks to wide gaps between the lugs.
- Due to the close spacing of the lugs in the centre of the tread, the rolling resistance can be reduced on hard surfaces.
- Matching chains and ribbons are available on the market.

Technical Informations

Item number	15212849
EAN	7291050056977
Valid tyre size	750 / 55 - 26.5
LI / SI / PR	184 A2 / 177 A8, 20 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Forestar 344
TRA Code	LS-2
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	251,81
Recommended rim size	24.00
Maximum air pressure [bar].	5,00
Section width (mm)	750
Outer diameter of tyre [mm].	1485
Stat. radius (SLR) [mm]	690
Rolling circumference [mm].	4554
Tread depth (mm)	46,0
Tyre capacity 75% [ltr.]	493.5
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
184 A2	9000	10		5,00	
177 A8	7300	40		5,00	