

TYRES

Product group	Tyres	
Item number	15212870	
Valid tyre size	800 / 45 - 26.5	
LI / SI / PR	164 A8 / 177 A8, 16 PR	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Flotation 328	





Notes and features

- Bias flotation tyre for towed vehicles.
- Soil-protecting tread pattern.

• Also for tractors (turf rolls).



Technical Informations

Item number	15212870
EAN	7291050039659
Valid tyre size	800 / 45 - 26.5
LI / SI / PR	164 A8 / 177 A8, 16 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Flotation 328
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	152,91
Recommended rim size	AG28.00
Maximum air pressure [bar].	2,20
Section width (mm)	800
Outer diameter of tyre [mm].	1393
Stat. radius (SLR) [mm]	614
Speed Radius Index (SRI)	650
Rolling circumference [mm].	4050
Tread depth (mm)	25,0
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
164 A8	5000	40	Drive Wheel	2,20	
177 A8	7300	40	Free Rolling	2,20	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.