

TYRES

Product group	Tyres	
Item number	15213513	
Valid tyre size	600 / 60 - 30.5	
LI / SI / PR	175 A2 / 168 A8, 20 PR	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Forestry 331	





Notes and features

- The Alliance Forestry 331 forest was developed for use on modern harvesters and transport vehicles in the forestry sector.
- It is also highly-suitable for mobile excavators, wheel loaders and dumpers working on difficult terrain.
- The tyre can also be used in agriculture for cultivating tough and abrasive surfaces.
- The tyre is characterised by high traction, low slip and low fuel consumption.
- Its huge volume ensures low soil compaction and good ride comfort in forestry and agricultural applications.
- Due to its strong nylon casing with steel belts, high undertread gauge, reinforced sidewalls and a sturdy rubber compound, the tyre is extremely robust and durable.



Technical Informations

Item number	15213513
EAN	7291050015165
Valid tyre size	600 / 60 - 30.5
LI / SI / PR	175 A2 / 168 A8, 20 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Forestry 331
TRA Code	13
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	201,96
Recommended rim size	20.00
Maximum air pressure [bar].	4,00
Section width (mm)	600
Outer diameter of tyre [mm].	1500
Stat. radius (SLR) [mm]	696
Rolling circumference [mm].	4504
Tread depth (mm)	39,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
175 A2	6900	10		4,00	
168 A8	5600	40		4,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.