Bohnenkamp Moving Professionals

22.09.2024

TYRES

Product group	Tyres	
Item number	15213612	
Valid tyre size	850 / 50 - 30.5	
LI / SI / PR	174 A8 / 186 A8, 16 PR	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Flotation 328	





Notes and features

- Bias flotation tyre for towed vehicles.
- Soil-protecting tread pattern.

• Also for tractors (turf rolls).

Bohnenkamp Moving Professionals

Technical Informations

	15010010
Item number	15213612
EAN	7291050010436
Valid tyre size	850 / 50 - 30.5
LI / SI / PR	174 A8 / 186 A8, 16 PR
TL/TT	TL
Brand	Alliance
Tread pattern	Flotation 328
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	231,78
Recommended rim size	28.00
Maximum air pressure [bar].	2,20
Section width (mm)	850
Outer diameter of tyre [mm].	1670
Stat. radius (SLR) [mm]	720
Rolling circumference [mm].	4790
Tread depth (mm)	25,0
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
174 A8	6700	40	Drive Wheel	2,20	
186 A8	9500	40	Free Rolling	2,20	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.