

TYRES

Product group	Tyres
Item number	15215505
Valid tyre size	500 / 50 R 17
LI / SI / PR	149 D
TL/TT	TL
Brand	Alliance
Tread pattern	882



Notes and features

- Newly-developed flotation tyre with steel belt reinforcement.
- Primary use on heavy transport vehicles and slurry tankers as well as manure spreaders with mixed road and field use.
- Directional block tread pattern for low rolling resistance and very good self-cleaning.
- High air volume for low soil compaction and high load-bearing capacity even with low inflation pressure.
- Steel belt offers additional protection against punctures.

Technical Informations

Item number	15215505
EAN	8903635021940
Valid tyre size	500 / 50 R 17
LI / SI / PR	149 D
TL/TT	TL
Brand	Alliance
Tread pattern	882
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	58,50
Recommended rim size	16.00
Maximum air pressure [bar].	5,00
Section width (mm)	503
Outer diameter of tyre [mm].	932
Stat. radius (SLR) [mm]	409
Rolling circumference [mm].	2833
Tread depth (mm)	15,0
Tyre capacity 75% [ltr.]	145.5
Guarantee period	10 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
149 D	3250	65		5,00	