

TYRES

Product group	Tyres
Item number	15215520
Valid tyre size	385 / 65 R 22.5
LI / SI / PR	164 D
TL/TT	TL
Brand	Alliance
Tread pattern	882



Notes and features

- Newly-developed flotation tyre with steel belt reinforcement.
- Primary use on heavy transport vehicles and slurry tankers as well as manure spreaders with mixed road and field use.
- Directional block tread pattern for low rolling resistance and very good self-cleaning.
- High air volume for low soil compaction and high load-bearing capacity even with low inflation pressure.
- Steel belt offers additional protection against punctures.

Technical Informations

Item number	15215520
EAN	8903635013877
Valid tyre size	385 / 65 R 22.5
LI / SI / PR	164 D
TL/TT	TL
Brand	Alliance
Tread pattern	882
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	80,58
Recommended rim size	11.75
Maximum air pressure [bar].	9,00
Section width (mm)	389
Outer diameter of tyre [mm].	1072
Stat. radius (SLR) [mm]	493
Rolling circumference [mm].	3205
Tread depth (mm)	12,7
Guarantee period	10 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
164 D	5000	65		9,00	