

TYRES

| | |
|-----------------|-----------------|
| Product group | Tyres |
| Item number | 15215522 |
| Valid tyre size | 560 / 45 R 22.5 |
| LI / SI / PR | 152 D |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | 882 |



 **ALLIANCE**

Notes and features

- Newly-developed flotation tyre with steel belt reinforcement.
- Primary use on heavy transport vehicles and slurry tankers as well as manure spreaders with mixed road and field use.
- Directional block tread pattern for low rolling resistance and very good self-cleaning.
- High air volume for low soil compaction and high load-bearing capacity even with low inflation pressure.
- Steel belt offers additional protection against punctures.

Technical Informations

| | |
|------------------------------|-----------------|
| Item number | 15215522 |
| EAN | 8903635013358 |
| Valid tyre size | 560 / 45 R 22.5 |
| LI / SI / PR | 152 D |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | 882 |
| Carcass properties | Steel Belted |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 89,13 |
| Recommended rim size | 16.00 |
| Maximum air pressure [bar]. | 4,00 |
| Section width (mm) | 550 |
| Outer diameter of tyre [mm]. | 1076 |
| Stat. radius (SLR) [mm] | 484 |
| Rolling circumference [mm]. | 3289 |
| Tread depth (mm) | 17,0 |
| Number of lugs | 28x2 |
| Guarantee period | 10 years |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 152 D | 3550 | 65 | | 4,00 | |