

TYRES

Product group	Tyres
Item number	15215530
Valid tyre size	560 / 60 R 22.5
LI / SI / PR	164 D
TL/TT	TL
Brand	Alliance
Tread pattern	390





Notes and features

- Ideal for longer transport and grassland use.
- Block tread pattern for smooth handling on long road journeys and soil protection when driving on grassland.
- Low rolling resistance for minimum fuel consumption.
- High tread depth for a long service life.
- Steel belt reinforcement for high load capacities and improved stability.



Technical Informations

Item number	15215530
EAN	7291050055246
Valid tyre size	560 / 60 R 22.5
LI / SI / PR	164 D
TL/TT	TL
Brand	Alliance
Tread pattern	390
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	120,50
Recommended rim size	16.00
Maximum air pressure [bar].	4,00
Section width (mm)	572
Outer diameter of tyre [mm].	1252
Stat. radius (SLR) [mm]	564
Rolling circumference [mm].	3840
Tread depth (mm)	19,0
Guarantee period	10 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
164 D	5000	65		4,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.