

TYRES

Product group	Tyres	
Item number	15215536	
Valid tyre size	VF 560 / 60 R 22.5	
LI / SI / PR	163 D TL Alliance	
TL/TT		
Brand		
Tread pattern	Agriflex 389 +	





Notes and features

- The Alliance Agriflex 389 + is a VF tyre for agricultural trailers and trucks converted for agricultural use.
- The tyre enables very high loading capacities at extremely low inflation pressures.
- Its contact area, which is 25% larger compared to a standard tyre, provides excellent traction and reduced fuel consumption.
- At the same time, soil compaction is reduced and the soil is optimally protected.
- Its special tread pattern provides good grip and outstanding self-cleaning properties.
- Its casing, reinforced by 3 steel belts is characterised by durability and resistance to damage.



Technical Informations

Item number	15215536
EAN	7291050080545
Valid tyre size	VF 560 / 60 R 22.5
LI / SI / PR	163 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agriflex 389 +
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	128,00
Recommended rim size	16.00
Maximum air pressure [bar].	2,80
Section width (mm)	565
Outer diameter of tyre [mm].	1250
Stat. radius (SLR) [mm]	538
Rolling circumference [mm].	3711
Tread depth (mm)	23,0
Number of lugs	20x2
Tyre capacity 75% [ltr.]	297
Guarantee period	10 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
163 D	4875	65		2,80	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.