

TYRES

Product group	Tyres
Item number	15215566
Valid tyre size	600 / 50 R 22.5
LI / SI / PR	166 F
TL/TT	TL
Brand	Alliance
Tread pattern	390



Notes and features

- Ideal for longer transport and grassland use.
- Block tread pattern for smooth handling on long road journeys and soil protection when driving on grassland.
- Low rolling resistance for minimum fuel consumption.
- High tread depth for a long service life.
- Steel belt reinforcement for high load capacities and improved stability.

Technical Informations

Item number	15215566
EAN	7291050058162
Valid tyre size	600 / 50 R 22.5
LI / SI / PR	166 F
TL/TT	TL
Brand	Alliance
Tread pattern	390
Carcass properties	All-Steel
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	138,16
Recommended rim size	20.00
Maximum air pressure [bar].	6,00
Section width (mm)	585
Outer diameter of tyre [mm].	1180
Stat. radius (SLR) [mm]	539
Rolling circumference [mm].	3510
Tread depth (mm)	25,0
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
166 F	5300	80		6,00	