

TYRES

| | |
|-----------------|-----------------|
| Product group | Tyres |
| Item number | 15215570 |
| Valid tyre size | 600 / 50 R 22.5 |
| LI / SI / PR | 162 D / 159 E |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | 390 |



Notes and features

- Ideal for longer transport and grassland use.
- Block tread pattern for smooth handling on long road journeys and soil protection when driving on grassland.
- Low rolling resistance for minimum fuel consumption.
- High tread depth for a long service life.
- Steel belt reinforcement for high load capacities and improved stability.

Technical Informations

| | |
|------------------------------|-----------------|
| Item number | 15215570 |
| EAN | 7291050022972 |
| Valid tyre size | 600 / 50 R 22.5 |
| LI / SI / PR | 162 D / 159 E |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | 390 |
| Carcass properties | Steel Belted |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 127.75 |
| Recommended rim size | 20.00 |
| Maximum air pressure [bar]. | 4,00 |
| Section width (mm) | 583 |
| Outer diameter of tyre [mm]. | 1171 |
| Stat. radius (SLR) [mm] | 531 |
| Rolling circumference [mm]. | 3605 |
| Tread depth (mm) | 24,5 |
| Guarantee period | 10 years |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 162 D | 4375 | 70 | | 4,00 | |
| 159 E | 4375 | 70 | | | |