

## **TYRES**

Product group	Tyres	
Item number	15215570	
Valid tyre size	600 / 50 R 22.5	
LI / SI / PR	162 D / 159 E	
TL/TT	TL	
Brand	Alliance	
Tread pattern	390	





## **Notes and features**

- Ideal for longer transport and grassland use.
- Block tread pattern for smooth handling on long road journeys and soil protection when driving on grassland.
- Low rolling resistance for minimum fuel consumption.
- High tread depth for a long service life.
- Steel belt reinforcement for high load capacities and improved stability.



## **Technical Informations**

Item number	15215570
EAN	7291050022972
Valid tyre size	600 / 50 R 22.5
LI / SI / PR	162 D / 159 E
TL/TT	TL
Brand	Alliance
Tread pattern	390
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	127.75
Recommended rim size	20.00
Maximum air pressure [bar].	4,00
Section width (mm)	583
Outer diameter of tyre [mm].	1171
Stat. radius (SLR) [mm]	531
Rolling circumference [mm].	3605
Tread depth (mm)	24,5
Guarantee period	10 years
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
162 D	4375	70		4,00	
159 E	4375	70			

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.