

TYRES

Product group	Tyres
Item number	15215572
Valid tyre size	600 / 50 R 22.5
LI / SI / PR	164 J
TL/TT	TL
Brand	Alliance
Tread pattern	382



Notes and features

- High-speed flotation tyre up to 100 km/h for use on agricultural trucks.
- All-steel casing for high load capacity and optimum transport capacity on long distance routes.
- Block tread pattern and high tread percentage for excellent ride comfort and reduced fuel consumption.
- Perfect for use on trucks in transport chains and for delivery vehicles.

Technical Informations

Item number	15215572
EAN	7291050060189
Valid tyre size	600 / 50 R 22.5
LI / SI / PR	164 J
TL/TT	TL
Brand	Alliance
Tread pattern	382
Carcass properties	All-Steel
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	135,65
Recommended rim size	20.00
Maximum air pressure [bar].	6,50
Section width (mm)	600
Outer diameter of tyre [mm].	1170
Stat. radius (SLR) [mm]	535
Rolling circumference [mm].	3587
Tread depth (mm)	25,0
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
164 J	5000	100		6,50	