

TYRES

Product group	Tyres
Item number	15215579
Valid tyre size	600 / 50 R 22.5
LI / SI / PR	167 D
TL/TT	TL
Brand	Alliance
Tread pattern	380 Industrial HD



Notes and features

- Flotation radial tyre for off-road transport applications, suitable for manure spreaders, field sprayers, articulated dumpers and agricultural trailers.
- Very good self-cleaning due to wide tread pattern spaces.
- The tyre provides all soil protection and flotation tyre properties for use in the field.
- Its special non-directional tread pattern enables excellent self-cleaning, uniform traction in the field and good ride comfort on short road trips.
- Its unique high-speed steel belted construction and its special rubber compound allow speeds up to 65 km/h when used on the road.
- HD-version with 3 steel belt plies, 5 nylon plies and reinforced bead for higher load capacity and durability compared with the standard tyre range.

Technical Informations

Item number	15215579
EAN	7291050067058
Valid tyre size	600 / 50 R 22.5
LI / SI / PR	167 D
TL/TT	TL
Brand	Alliance
Tread pattern	380 Industrial HD
Carcass properties	Steel Belted,HD
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	126,80
Recommended rim size	20.00
Maximum air pressure [bar].	5,00
Section width (mm)	611
Outer diameter of tyre [mm].	1172
Stat. radius (SLR) [mm]	527
Rolling circumference [mm].	3588
Tread depth (mm)	25,0
Guarantee period	10 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
167 D	5450	65		5,00	