

## TYRES

Product group	Tyres
Item number	15215580
Valid tyre size	600 / 50 R 22.5
LI / SI / PR	164 J
TL/TT	TL
Brand	Alliance
Tread pattern	380



## Notes and features

- Flotation radial tyres with steel belt reinforcement for off-road transport work.
- Very good self-cleaning due to wide tread pattern spaces.
- Large air volume enables high load capacities even with low inflation pressures for use that is gentle on the soil.
- Its special non-directional tread pattern enables very good self-cleaning and uniform traction in the field.
- The tyre is only suitable for short transport journeys on the road.
- Ideal for manure spreaders, slurry tankers and vehicles used on construction sites.

## Technical Informations

Item number	15215580
EAN	7291050060820
Valid tyre size	600 / 50 R 22.5
LI / SI / PR	164 J
TL/TT	TL
Brand	Alliance
Tread pattern	380
Carcass properties	All-Steel
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	136,71
Recommended rim size	20.00
Maximum air pressure [bar].	6,50
Section width (mm)	608
Outer diameter of tyre [mm].	1172
Stat. radius (SLR) [mm]	527
Rolling circumference [mm].	3611
Tread depth (mm)	25,0
Guarantee period	7 years
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
164 J	5000	100		6,50	