

## TYRES

Product group	Tyres
Item number	15215600
Valid tyre size	560 / 60 R 22.5
LI / SI / PR	164 D / 161 E
TL/TT	TL
Brand	Alliance
Tread pattern	380



## Notes and features

- Flotation radial tyres with steel belt reinforcement for off-road transport work.
- Very good self-cleaning due to wide tread pattern spaces.
- Large air volume enables high load capacities even with low inflation pressures for use that is gentle on the soil.
- Its special non-directional tread pattern enables very good self-cleaning and uniform traction in the field.
- The tyre is only suitable for short transport journeys on the road.
- Ideal for manure spreaders, slurry tankers and vehicles used on construction sites.

## Technical Informations

Item number	15215600
EAN	8903635013112
Valid tyre size	560 / 60 R 22.5
LI / SI / PR	164 D / 161 E
TL/TT	TL
Brand	Alliance
Tread pattern	380
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	116,65
Recommended rim size	16.00
Maximum air pressure [bar].	4,00
Section width (mm)	564
Outer diameter of tyre [mm].	1244
Stat. radius (SLR) [mm]	555.00
Rolling circumference [mm].	3773
Tread depth (mm)	23,0
Tyre capacity 75% [ltr.]	300
Guarantee period	10 years
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
164 D	4625	70		4,00	
161 E	4625	70			