

TYRES

Product group	Tyres
Item number	15215650
Valid tyre size	650 / 50 R 22.5
LI / SI / PR	166 D / 163 E
TL/TT	TL
Brand	Alliance
Tread pattern	380



Notes and features

- Flotation radial tyres with steel belt reinforcement for off-road transport work.
- Very good self-cleaning due to wide tread pattern spaces.
- Large air volume enables high load capacities even with low inflation pressures for use that is gentle on the soil.
- Its special non-directional tread pattern enables very good self-cleaning and uniform traction in the field.
- The tyre is only suitable for short transport journeys on the road.
- Ideal for manure spreaders, slurry tankers and vehicles used on construction sites.

Technical Informations

Item number	15215650
EAN	7291050022330
Valid tyre size	650 / 50 R 22.5
LI / SI / PR	166 D / 163 E
TL/TT	TL
Brand	Alliance
Tread pattern	380
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	129.90
Recommended rim size	AG20.00
Maximum air pressure [bar].	4,00
Section width (mm)	650
Outer diameter of tyre [mm].	1240
Stat. radius (SLR) [mm]	554
Rolling circumference [mm].	3798
Tread depth (mm)	26,0
Lug width (mm)	66
Guarantee period	10 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
166 E	4875	70		4,00	
163	4875				