

TYRES

Product group	Tyres
Item number	15215657
Valid tyre size	710 / 45 R 22.5
LI / SI / PR	165 D
TL/TT	TL
Brand	Alliance
Tread pattern	380



Notes and features

- Flotation radial tyres with steel belt reinforcement for off-road transport work.
- Very good self-cleaning due to wide tread pattern spaces.
- Large air volume enables high load capacities even with low inflation pressures for use that is gentle on the soil.
- Its special non-directional tread pattern enables very good self-cleaning and uniform traction in the field.
- The tyre is only suitable for short transport journeys on the road.
- Ideal for manure spreaders, slurry tankers and vehicles used on construction sites.

Technical Informations

Item number	15215657
EAN	7291050068840
Valid tyre size	710 / 45 R 22.5
LI / SI / PR	165 D
TL/TT	TL
Brand	Alliance
Tread pattern	380
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	136,93
Recommended rim size	24.00
Maximum air pressure [bar].	4,00
Section width (mm)	727
Outer diameter of tyre [mm].	1210
Stat. radius (SLR) [mm]	534
Rolling circumference [mm].	3683
Tread depth (mm)	26,0
Tyre capacity 75% [ltr.]	356.25
Guarantee period	10 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
165 D	5150	65		4,00	