

TYRES

Product group	Tyres	
Item number	15215670	
Valid tyre size	620 / 75 R 26	
LI / SI / PR	174 D	
TL/TT	TL	
Brand	Alliance	
Tread pattern	390	





Notes and features

- Ideal for longer transport and grassland use.
- Block tread pattern for smooth handling on long road journeys and soil protection when driving on grassland.
- Low rolling resistance for minimum fuel consumption.
- High tread depth for a long service life.
- Steel belt reinforcement for high load capacities and improved stability.



Technical Informations

Item number	15215670
EAN	7291050057967
Valid tyre size	620 / 75 R 26
Alternative size 1	23.1R26
LI / SI / PR	174 D
TL/TT	TL
Brand	Alliance
Tread pattern	390
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	192,98
Recommended rim size	20
Maximum air pressure [bar].	4,00
Section width (mm)	620
Outer diameter of tyre [mm].	1590
Stat. radius (SLR) [mm]	707
Rolling circumference [mm].	4721
Tread depth (mm)	26,0
Tyre capacity 75% [ltr.]	748
Guarantee period	10 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
174 D	6700	65		4,00	