

TYRES

Product group	Tyres
Item number	15215743
Valid tyre size	650 / 65 R 26.5
LI / SI / PR	165 D
TL/TT	TL
Brand	Alliance
Tread pattern	388



Notes and features

- All-round flotation tyre for mixed usage with medium load volumes.
- Traction tread pattern with overlapping centre lugs for optimum ride comfort and good self-cleaning.
- High load capacity even at low inflation pressure allows outstanding soil protection.
- Steel belt reinforcement offers additional protection against punctures.

Technical Informations

Item number	15215743
EAN	7291050060554
Valid tyre size	650 / 65 R 26.5
LI / SI / PR	165 D
TL/TT	TL
Brand	Alliance
Tread pattern	388
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	160,03
Recommended rim size	20.00
Maximum air pressure [bar].	2,80
Section width (mm)	651
Outer diameter of tyre [mm].	1500
Stat. radius (SLR) [mm]	661
Rolling circumference [mm].	4509
Tread depth (mm)	25,0
Guarantee period	10 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
165 D	5150	65		2,80	