

TYRES

| | |
|-----------------|-----------------|
| Product group | Tyres |
| Item number | 15215747 |
| Valid tyre size | 710 / 50 R 26.5 |
| LI / SI / PR | 170 D |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | 380 |



Notes and features

- Flotation radial tyres with steel belt reinforcement for off-road transport work.
- Very good self-cleaning due to wide tread pattern spaces.
- Large air volume enables high load capacities even with low inflation pressures for use that is gentle on the soil.
- Its special non-directional tread pattern enables very good self-cleaning and uniform traction in the field.
- The tyre is only suitable for short transport journeys on the road.
- Ideal for manure spreaders, slurry tankers and vehicles used on construction sites.

Technical Informations

| | |
|------------------------------|-----------------|
| Item number | 15215747 |
| EAN | 7291050065405 |
| Valid tyre size | 710 / 50 R 26.5 |
| LI / SI / PR | 170 D |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | 380 |
| Carcass properties | Steel Belted |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 172,60 |
| Recommended rim size | 24.00 |
| Maximum air pressure [bar]. | 4,00 |
| Section width (mm) | 732 |
| Outer diameter of tyre [mm]. | 1400 |
| Stat. radius (SLR) [mm] | 630 |
| Speed Radius Index (SRI) | 675 |
| Rolling circumference [mm]. | 4290 |
| Tread depth (mm) | 26,0 |
| Number of lugs | 22x2 |
| Tyre capacity 75% [ltr.] | 470 |
| Guarantee period | 10 years |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 170 D | 6000 | 65 | | 4,00 | |