

TYRES

Product group	Tyres	
Item number	15215790	
Valid tyre size	600 / 60 R 30.5	
LI / SI / PR	173 D	
TL/TT	TL	
Brand	Alliance	
Tread pattern	390	





Notes and features

- Ideal for longer transport and grassland use.
- Block tread pattern for smooth handling on long road journeys and soil protection when driving on grassland.
- Low rolling resistance for minimum fuel consumption.
- High tread depth for a long service life.
- Steel belt reinforcement for high load capacities and improved stability.



Technical Informations

Item number	15215790
EAN	7291050022934
Valid tyre size	600 / 60 R 30.5
LI / SI / PR	173 D
TL/TT	TL
Brand	Alliance
Tread pattern	390
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	182,53
Recommended rim size	AG20.00
Permitted rim size	20
Maximum air pressure [bar].	4,00
Section width (mm)	600
Outer diameter of tyre [mm].	1506
Stat. radius (SLR) [mm]	693
Dynamic radius [mm]	702.5
Speed Radius Index (SRI)	725
Rolling circumference [mm].	4587
Tread depth (mm)	25,5
Guarantee period	10 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
173 D	6500	65		4,00	