

## TYRES

Product group	Tyres
Item number	15215793
Valid tyre size	650 / 65 R 30.5
LI / SI / PR	176 D
TL/TT	TL
Brand	Alliance
Tread pattern	380



## Notes and features

- Flotation radial tyres with steel belt reinforcement for off-road transport work.
- Very good self-cleaning due to wide tread pattern spaces.
- Large air volume enables high load capacities even with low inflation pressures for use that is gentle on the soil.
- Its special non-directional tread pattern enables very good self-cleaning and uniform traction in the field.
- The tyre is only suitable for short transport journeys on the road.
- Ideal for manure spreaders, slurry tankers and vehicles used on construction sites.

## Technical Informations

Item number	15215793
EAN	7291050048675
Valid tyre size	650 / 65 R 30.5
LI / SI / PR	176 D
TL/TT	TL
Brand	Alliance
Tread pattern	380
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	200,27
Recommended rim size	20.00
Maximum air pressure [bar].	4,00
Section width (mm)	680
Outer diameter of tyre [mm].	1625
Stat. radius (SLR) [mm]	726
Speed Radius Index (SRI)	775
Rolling circumference [mm].	4881
Tread depth (mm)	26,0
Tyre capacity 75% [litr.]	579
Guarantee period	10 years
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
176 D	7100	65		4,00	