

## TYRES

Product group	Tyres
Item number	15215794
Valid tyre size	650 / 65 R 30.5
LI / SI / PR	181 D
TL/TT	TL
Brand	Alliance
Tread pattern	380 Industrial HD



## Notes and features

- Flotation radial tyre for off-road transport applications, suitable for manure spreaders, field sprayers, articulated dumpers and agricultural trailers.
- Very good self-cleaning due to wide tread pattern spaces.
- The tyre provides all soil protection and flotation tyre properties for use in the field.
- Its special non-directional tread pattern enables excellent self-cleaning, uniform traction in the field and good ride comfort on short road trips.
- Its unique high-speed steel belted construction and its special rubber compound allow speeds up to 65 km/h when used on the road.
- HD-version with 3 steel belt plies, 5 nylon plies and reinforced bead for higher load capacity and durability compared with the standard tyre range.

## Technical Informations

Item number	15215794
EAN	7291050057455
Valid tyre size	650 / 65 R 30.5
LI / SI / PR	181 D
TL/TT	TL
Brand	Alliance
Tread pattern	380 Industrial HD
Carcass properties	HD,Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	221,76
Recommended rim size	20.00
Maximum air pressure [bar].	5,00
Section width (mm)	676
Outer diameter of tyre [mm].	1628
Stat. radius (SLR) [mm]	741
Rolling circumference [mm].	4881
Tread depth (mm)	26,0
Tyre capacity 75% [ltr.]	772
Guarantee period	10 years
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
181 D	8250	65		5,00	