

TYRES

| Product group | Tyres | |
|-----------------|-------------------|--|
| Item number | 15215796 | |
| Valid tyre size | 710 / 50 R 30.5 | |
| LI / SI / PR | 184 D | |
| TL/TT | TL | |
| Brand | Alliance | |
| Tread pattern | 390 Industrial HD | |





Notes and features

- The Alliance 390 HD is ideal for longer transport and grassland use.
- Its non-directional block tread pattern enables smooth driving during longer road journeys and protects the soil when driving on grassland.
- The low rolling resistance minimises fuel consumption.
- The high tread pattern depth ensures the tyre has a long service life.
- The HD version with 4 steel belts and specially reinforced bead enables higher loading capacities and better durability compared with the standard tyre.



Technical Informations

| Item number | 15215796 |
|------------------------------|-------------------|
| EAN | 7291050057493 |
| Valid tyre size | 710 / 50 R 30.5 |
| LI / SI / PR | 184 D |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | 390 Industrial HD |
| Carcass properties | HD,Steel Belted |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 228,36 |
| Recommended rim size | 24.00 |
| Maximum air pressure [bar]. | 5,00 |
| Section width (mm) | 725 |
| Outer diameter of tyre [mm]. | 1502 |
| Stat. radius (SLR) [mm] | 676 |
| Dynamic radius [mm] | 698.1 |
| Rolling circumference [mm]. | 4576 |
| Tread depth (mm) | 26,0 |
| Number of lugs | 30x2 |
| Tyre capacity 75% [ltr.] | 506 |
| Guarantee period | 10 years |
| E-Ready | No |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 184 D | 9000 | 65 | | 5,00 | |