

TYRES

Product group	Tyres
Item number	15215801
Valid tyre size	750 / 60 R 30.5
LI / SI / PR	190 D
TL/TT	TL
Brand	Alliance
Tread pattern	390 Industrial HD





Notes and features

- The Alliance 390 HD is ideal for longer transport and grassland use.
- Its non-directional block tread pattern enables smooth driving during longer road journeys and protects the soil when driving on grassland.
- The low rolling resistance minimises fuel consumption.
- The high tread pattern depth ensures the tyre has a long service life.
- The HD version with 4 steel belts and specially reinforced bead enables higher loading capacities and better durability compared with the standard tyre.



Technical Informations

Item number	15215801
EAN	7291050057363
Valid tyre size	750 / 60 R 30.5
LI / SI / PR	190 D
TL/TT	TL
Brand	Alliance
Tread pattern	390 Industrial HD
Carcass properties	HD,Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	282,40
Recommended rim size	24.00
Maximum air pressure [bar].	6,00
Section width (mm)	770
Outer diameter of tyre [mm].	1700
Stat. radius (SLR) [mm]	751
Rolling circumference [mm].	5136
Tread depth (mm)	26,0
Guarantee period	10 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
190 D	10600	65		6,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.