

TYRES

Product group	Tyres
Item number	15215805
Valid tyre size	750 / 60 R 30.5
LI / SI / PR	181 D
TL/TT	TL
Brand	Alliance
Tread pattern	380





Notes and features

- Flotation radial tyres with steel belt reinforcement for offroad transport work.
- Very good self-cleaning due to wide tread pattern spaces.
- Large air volume enables high load capacities even with low inflation pressures for use that is gentle on the soil.
- Its special non-directional tread pattern enables very good self-cleaning and uniform traction in the field.
- The tyre is only suitable for short transport journeys on the road.
- Ideal for manure spreaders, slurry tankers and vehicles used on construction sites.



Technical Informations

Item number	15215805
EAN	7291050068666
Valid tyre size	750 / 60 R 30.5
LI / SI / PR	181 D
TL/TT	TL
Brand	Alliance
Tread pattern	380
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	235,12
Recommended rim size	AG24.00
Maximum air pressure [bar].	4,00
Section width (mm)	763
Outer diameter of tyre [mm].	1687
Stat. radius (SLR) [mm]	754
Rolling circumference [mm].	5145
Tread depth (mm)	26,0
Number of lugs	26x2
Tyre capacity 75% [ltr.]	734.25
Guarantee period	10 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
181 D	8250	65		4,00	