

## TYRES

|                 |                  |
|-----------------|------------------|
| Product group   | Tyres            |
| Item number     | 15215819         |
| Valid tyre size | VF 800 / 60 R 32 |
| LI / SI / PR    | 188 D            |
| TL/TT           | TL               |
| Brand           | Alliance         |
| Tread pattern   | Agriflex 389 +   |



## Notes and features

- The Alliance Agriflex 389 + is a VF tyre for agricultural trailers and trucks converted for agricultural use.
- The tyre enables very high loading capacities at extremely low inflation pressures.
- Its contact area, which is 25% larger compared to a standard tyre, provides excellent traction and reduced fuel consumption.
- At the same time, soil compaction is reduced and the soil is optimally protected.
- Its special tread pattern provides good grip and outstanding self-cleaning properties.
- Its casing, reinforced by 3 steel belts is characterised by durability and resistance to damage.

## Technical Informations

|                              |                  |
|------------------------------|------------------|
| Item number                  | 15215819         |
| EAN                          | 7291050083393    |
| Valid tyre size              | VF 800 / 60 R 32 |
| LI / SI / PR                 | 188 D            |
| TL/TT                        | TL               |
| Brand                        | Alliance         |
| Tread pattern                | Agriflex 389 +   |
| Carcass properties           | Steel Belted     |
| Antistatic                   | No               |
| Tyre colour                  | Black            |
| ECE regulation number        | ECE 106          |
| Nettogewicht [kg] (gültig)   | 278.70           |
| Recommended rim size         | DW27B            |
| Permitted rim size           | TW27B            |
| Maximum air pressure [bar].  | 2,80             |
| Section width (mm)           | 800              |
| Outer diameter of tyre [mm]. | 1800             |
| Stat. radius (SLR) [mm]      | 778              |
| Rolling circumference [mm].  | 5465             |
| Tread depth (mm)             | 26,0             |
| Number of lugs               | 28x2             |
| Tyre capacity 75% [ltr.]     | 877.5            |
| E-Ready                      | No               |

## Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 188 D | 10000              | 65           |               | 2,80                     |              |