Bohnenkamp Moving Professionals

05.02.2025

TYRES

Product group	Tyres
Item number	15215830
Valid tyre size	30.5L R 32
LI / SI / PR	181 B
TL/TT	TL
Brand	Alliance
Tread pattern	390





Notes and features

- Ideal for longer transport and grassland use.
- Block tread pattern for smooth handling on long road journeys and soil protection when driving on grassland.
- Low rolling resistance for minimum fuel consumption.
- High tread depth for a long service life.
- Steel belt reinforcement for high load capacities and improved stability.

Bohnenkamp Moving Professionals

Technical Informations

Item number	15215830
EAN	7291050022897
Valid tyre size	30.5L R 32
LI / SI / PR	181 B
TL/TT	ТL
Brand	Alliance
Tread pattern	390
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	272,64
Recommended rim size	27
Maximum air pressure [bar].	3,00
Section width (mm)	790
Outer diameter of tyre [mm].	1800
Stat. radius (SLR) [mm]	805
Rolling circumference [mm].	5431
Tread depth (mm)	30,0
Tyre capacity 75% [ltr.]	1073
Guarantee period	10 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
181 B	8250	50		3,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.