

TYRES

Product group	Tyres
Item number	15215836
Valid tyre size	35.5L R 32
LI / SI / PR	193 A8 / 190 D
TL/TT	TL
Brand	Alliance
Tread pattern	393



Notes and features

- Newly-developed flotation tyre with steel belt reinforcement.
- Primary use on heavy transport vehicles and slurry tankers as well as transfer vehicles in mixed road and field use.
- Directional block tread pattern for low rolling resistance and very good self-cleaning.
- High air volume for low soil compaction and high load-bearing capacity even with low inflation pressure.
- Steel belt offers additional protection against punctures.

Technical Informations

Item number	15215836
EAN	7291050061773
Valid tyre size	35.5L R 32
Alternative size 1	900/65R32
LI / SI / PR	193 A8 / 190 D
TL/TT	TL
Brand	Alliance
Tread pattern	393
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	372,33
Recommended rim size	31
Permitted rim size	30
Maximum air pressure [bar].	3,00
Section width (mm)	925
Outer diameter of tyre [mm].	1986
Stat. radius (SLR) [mm]	864
Rolling circumference [mm].	5952
Tread depth (mm)	40,0
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
193 A8	11500	40		3,00	
190 D	10600	65		3,00	