

TYRES

Product group	Tyres
Item number	15215855
Valid tyre size	650 / 60 R 34
LI / SI / PR	175 D
TL/TT	TL
Brand	Alliance
Tread pattern	388



Notes and features

- All-round flotation tyre for mixed usage with medium load volumes.
- Traction tread pattern with overlapping centre lugs for optimum ride comfort and good self-cleaning.
- High load capacity even at low inflation pressure allows outstanding soil protection.
- Steel belt reinforcement offers additional protection against punctures.

Technical Informations

Item number	15215855
EAN	7291050059947
Valid tyre size	650 / 60 R 34
LI / SI / PR	175 D
TL/TT	TL
Brand	Alliance
Tread pattern	388
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	184,27
Recommended rim size	20
Permitted rim size	18, 23
Maximum air pressure [bar].	4,00
Section width (mm)	660
Outer diameter of tyre [mm].	1650
Stat. radius (SLR) [mm]	760
Rolling circumference [mm].	5117
Tread depth (mm)	27,0
Guarantee period	10 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
175 D	6900	65		4,00	