

TYRES

Product group	Tyres
Item number	15216080
Valid tyre size	500 / 45 R 20
LI / SI / PR	145 A8 / 157 A8
TL/TT	TL
Brand	Alliance
Tread pattern	381



Notes and features

- Steel belted tyre for use on grassland.
- Rounded shoulders for optimum soil and turf protection.
- Non-directional tread pattern.
- Low soil compaction due to large contact area.
- High tread pattern percentage and low rolling resistance for optimum fuel efficiency.
- Ideal for silage trailers and transport vehicles for green fodder harvesting.

Technical Informations

Item number	15216080
EAN	8903635017691
Valid tyre size	500 / 45 R 20
LI / SI / PR	145 A8 / 157 A8
TL/TT	TL
Brand	Alliance
Tread pattern	381
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	58,00
Recommended rim size	16
Maximum air pressure [bar].	4,00
Section width (mm)	502
Outer diameter of tyre [mm].	958
Stat. radius (SLR) [mm]	412
Rolling circumference [mm].	2877
Tread depth (mm)	14,5
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
145 A8	2900	40	Drive Wheel	4,00	LLV
157 A8	4125	40	Free Rolling	4,00	LLV