

TYRES

Product group	Tyres
Item number	15216110
Valid tyre size	560 / 45 R 22.5
LI / SI / PR	146 D
TL/TT	TL
Brand	Alliance
Tread pattern	Flotmaster 381





Notes and features

- Steel belted tyre for use on grassland.
- Rounded shoulders for optimum soil and turf protection.
- Non-directional tread pattern.
- Low soil compaction due to large contact area.
- High tread pattern percentage and low rolling resistance for optimum fuel efficiency.
- Ideal for silage trailers and transport vehicles for green fodder harvesting.



Technical Informations

Item number	15216110
EAN	7291050057462
Valid tyre size	560 / 45 R 22.5
LI / SI / PR	146 D
TL/TT	TL
Brand	Alliance
Tread pattern	Flotmaster 381
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	84,87
Recommended rim size	16.00
Maximum air pressure [bar].	3,20
Section width (mm)	540
Outer diameter of tyre [mm].	1080
Stat. radius (SLR) [mm]	485
Rolling circumference [mm].	3304
Tread depth (mm)	18,5
Guarantee period	10 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
146 D	3000	65		3,20	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.