

TYRES

Product group	Tyres
Item number	15216131
Valid tyre size	620 / 40 R 22.5
LI / SI / PR	148 D
TL/TT	TL
Brand	Alliance
Tread pattern	Flotmaster 381



Notes and features

- Steel belted tyre for use on grassland.
- Rounded shoulders for optimum soil and turf protection.
- Non-directional tread pattern.
- Low soil compaction due to large contact area.
- High tread pattern percentage and low rolling resistance for optimum fuel efficiency.
- Ideal for silage trailers and transport vehicles for green fodder harvesting.

Technical Informations

Item number	15216131
EAN	8903635012672
Valid tyre size	620 / 40 R 22.5
LI / SI / PR	148 D
TL/TT	TL
Brand	Alliance
Tread pattern	Flotmaster 381
Carcass properties	Textil Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	87,13
Recommended rim size	20.00
Maximum air pressure [bar].	3,20
Section width (mm)	612
Outer diameter of tyre [mm].	1080
Stat. radius (SLR) [mm]	486
Rolling circumference [mm].	3295
Tread depth (mm)	18,0
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
148 D	3150	65		3,20	