

TYRES

Product group	Tyres	
Item number	15216163	
Valid tyre size	710 / 40 R 22.5	
LI / SI / PR	162 D	
TL/TT	TL	
Brand	Alliance	
Tread pattern	Flotmaster 381	





Notes and features

- Steel belted tyre for use on grassland.
- Rounded shoulders for optimum soil and turf protection.
- Non-directional tread pattern.
- Low soil compaction due to large contact area.
- High tread pattern percentage and low rolling resistance for optimum fuel efficiency.
- Ideal for silage trailers and transport vehicles for green fodder harvesting.



Technical Informations

Item number	15216163
EAN	7291050060295
Valid tyre size	710 / 40 R 22.5
LI / SI / PR	162 D
TL/TT	TL
Brand	Alliance
Tread pattern	Flotmaster 381
Carcass properties	Textil Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	109,52
Recommended rim size	24.00
Maximum air pressure [bar].	4,00
Section width (mm)	702
Outer diameter of tyre [mm].	1161
Stat. radius (SLR) [mm]	521
Rolling circumference [mm].	3582
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
162 D	4750	65		4,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.