

TYRES

Product group	Tyres
Item number	15216170
Valid tyre size	620 / 55 R 26.5
LI / SI / PR	166 D
TL/TT	TL
Brand	Alliance
Tread pattern	Flotmaster 381



Notes and features

- Steel belted tyre for use on grassland.
- Rounded shoulders for optimum soil and turf protection.
- Non-directional tread pattern.
- Low soil compaction due to large contact area.
- High tread pattern percentage and low rolling resistance for optimum fuel efficiency.
- Ideal for silage trailers and transport vehicles for green fodder harvesting.

Technical Informations

Item number	15216170
EAN	8903635021575
Valid tyre size	620 / 55 R 26.5
LI / SI / PR	166 D
TL/TT	TL
Brand	Alliance
Tread pattern	Flotmaster 381
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	131,80
Recommended rim size	20.00
Maximum air pressure [bar].	4,00
Section width (mm)	612
Outer diameter of tyre [mm].	1356
Stat. radius (SLR) [mm]	608
Rolling circumference [mm].	4147
Tread depth (mm)	19,0
Guarantee period	10 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
166 D	5300	65		4,00	