

TYRES

| | |
|-----------------|-----------------|
| Product group | Tyres |
| Item number | 15216225 |
| Valid tyre size | 560 / 60 R 22.5 |
| LI / SI / PR | 164 D |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | 885 |



Notes and features

- The Alliance 885 was developed for balers, grain wagons, cultivators, small agricultural trailers and similar towed vehicles.
- The rounded tyre shoulder and large contact area protect crops and soil from damage.
- The large lugs in the middle of the tread provide comfortable handling during transport journeys.
- Its low rolling resistance reduces fuel consumption.
- Thanks to the reinforced sidewall and the strong casing with steel belts, the tyre is optimally protected against damages.

Technical Informations

| | |
|------------------------------|-----------------|
| Item number | 15216225 |
| EAN | 8903635011095 |
| Valid tyre size | 560 / 60 R 22.5 |
| LI / SI / PR | 164 D |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | 885 |
| Carcass properties | Steel Belted |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 102,00 |
| Recommended rim size | AG 16.00 |
| Maximum air pressure [bar]. | 4,00 |
| Section width (mm) | 555 |
| Outer diameter of tyre [mm]. | 1230 |
| Stat. radius (SLR) [mm] | 553 |
| Speed Radius Index (SRI) | 575 |
| Rolling circumference [mm]. | 3620 |
| Tread depth (mm) | 19,5 |
| Guarantee period | 10 years |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 164 D | 5000 | 65 | | 4,00 | |