

## TYRES

Product group	Tyres
Item number	15216241
Valid tyre size	600 / 50 R 22.5
LI / SI / PR	159 D
TL/TT	TL
Brand	Alliance
Tread pattern	885



## Notes and features

- The Alliance 885 was developed for balers, grain wagons, cultivators, small agricultural trailers and similar towed vehicles.
- The rounded tyre shoulder and large contact area protect crops and soil from damage.
- The large lugs in the middle of the tread provide comfortable handling during transport journeys.
- Its low rolling resistance reduces fuel consumption.
- Thanks to the reinforced sidewall and the strong casing with steel belts, the tyre is optimally protected against damages.

## Technical Informations

Item number	15216241
EAN	8903635013181
Valid tyre size	600 / 50 R 22.5
LI / SI / PR	159 D
TL/TT	TL
Brand	Alliance
Tread pattern	885
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	104,13
Recommended rim size	20.00
Maximum air pressure [bar].	4,00
Section width (mm)	600
Outer diameter of tyre [mm].	1172
Stat. radius (SLR) [mm]	517.00
Speed Radius Index (SRI)	550
Rolling circumference [mm].	3537
Tread depth (mm)	19,5
Guarantee period	10 years
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
159 D	4375	65		4,00	