

TYRES

Product group	Tyres
Item number	15216252
Valid tyre size	650 / 65 R 26.5
LI / SI / PR	174 D
TL/TT	TL
Brand	Alliance
Tread pattern	885



Notes and features

- The Alliance 885 was developed for balers, grain wagons, cultivators, small agricultural trailers and similar towed vehicles.
- The rounded tyre shoulder and large contact area protect crops and soil from damage.
- The large lugs in the middle of the tread provide comfortable handling during transport journeys.
- Its low rolling resistance reduces fuel consumption.
- Thanks to the reinforced sidewall and the strong casing with steel belts, the tyre is optimally protected against damages.

Technical Informations

Item number	15216252
EAN	8903635017592
Valid tyre size	650 / 65 R 26.5
LI / SI / PR	174 D
TL/TT	TL
Brand	Alliance
Tread pattern	885
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	165,00
Recommended rim size	20.00
Maximum air pressure [bar].	4,00
Section width (mm)	645
Outer diameter of tyre [mm].	1519
Stat. radius (SLR) [mm]	670
Rolling circumference [mm].	4580
Tread depth (mm)	26,8
Number of lugs	24x2
Guarantee period	10 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
174 D	6700	65		4,00	