

## **TYRES**

| Product group   | Tyres           |  |
|-----------------|-----------------|--|
| Item number     | 15216255        |  |
| Valid tyre size | 710 / 50 R 26.5 |  |
| LI / SI / PR    | 170 D           |  |
| TL/TT           | TL              |  |
| Brand           | Alliance        |  |
| Tread pattern   | 885             |  |





## Notes and features

- The Alliance 885 was developed for balers, grain wagons, cultivators, small agricultural trailers and similar towed vehicles.
- The rounded tyre shoulder and large contact area protect crops and soil from damage.
- The large lugs in the middle of the tread provide comfortable handling during transport journeys.
- Its low rolling resistance reduces fuel consumption.
- Thanks to the reinforced sidewall and the strong casing with steel belts, the tyre is optimally protected against damages.



## **Technical Informations**

| Item number                  | 15216255        |
|------------------------------|-----------------|
| EAN                          | 8903635015581   |
| Valid tyre size              | 710 / 50 R 26.5 |
| LI / SI / PR                 | 170 D           |
| TL/TT                        | TL              |
| Brand                        | Alliance        |
| Tread pattern                | 885             |
| Carcass properties           | Steel Belted    |
| Antistatic                   | No              |
| Tyre colour                  | Black           |
| ECE regulation number        | ECE 106         |
| Nettogewicht [kg] (gültig)   | 168,12          |
| Recommended rim size         | AG24.00         |
| Maximum air pressure [bar].  | 4,00            |
| Section width (mm)           | 733             |
| Outer diameter of tyre [mm]. | 1390            |
| Stat. radius (SLR) [mm]      | 629             |
| Dynamic radius [mm]          | 647.1           |
| Speed Radius Index (SRI)     | 650             |
| Rolling circumference [mm].  | 4290            |
| Tread depth (mm)             | 26,0            |
| Number of lugs               | 21x2            |
| Guarantee period             | 10 years        |
| E-Ready                      | No              |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



## **Load capacity**

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure<br>[bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 170 D | 6000               | 65           |               | 4,00                        |              |