

TYRES

Product group	Tyres
Item number	15216332
Valid tyre size	495 / 70 R 24
LI / SI / PR	155 J
TL/TT	TL
Brand	Alliance
Tread pattern	398



Notes and features

- The Alliance 398 is a POR (Professional Off Road) tyre for use on agri-trucks in all weather and soil conditions.
- It is suitable for field applications as well as for road transport at speeds up to 100 km/h.
- In field use, the traction tread pattern provides very good self-cleaning properties, high traction and low soil compaction.
- The all-steel casing with 4 steel belt inserts guarantees excellent stability and a long service life.
- During road transport, the tyre stands out with low temperature development, low vibration and low noise.
- For road use with speeds of 100 km/h, the inflation pressure must be increased according to the manufacturer's inflation table.
- The tyre is also suited to forestry applications and can be used in wood chip production and in the construction and maintenance of forest paths.
- Use with a tyre pressure control system is possible.
- The tyre is very compatible with the Alligator tyre management.

Technical Informations

Item number	15216332
EAN	7291050072861
Valid tyre size	495 / 70 R 24
LI / SI / PR	155 J
TL/TT	TL
Brand	Alliance
Tread pattern	398
Carcass properties	All-Steel,POR
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	140,00
Recommended rim size	W16L
Permitted rim size	W15L, DW16L, W14L
Maximum air pressure [bar].	4,50
Section width (mm)	512
Outer diameter of tyre [mm].	1310
Stat. radius (SLR) [mm]	603
Rolling circumference [mm].	3849
Tread depth (mm)	37,0
Number of lugs	18x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
155 J	3875	100		4,50	