

TYRES

Product group	Tyres
Item number	15222050
Valid tyre size	6.50 - 16
LI / SI / PR	105 A6 / 101 A8, 8 PR
TL/TT	TT
Brand	Alliance
Tread pattern	324



Notes and features

- Agricultural bias tyre for use on tractors or as an implement tyre.
- Lugs at a 45° angle for high traction and good self-cleaning, even in the harshest operating conditions.
- The strong nylon casing ensures high operational safety and good traction transmission.

Technical Informations

Item number	15222050
EAN	8903635001522
Valid tyre size	6.50 - 16
LI / SI / PR	105 A6 / 101 A8, 8 PR
TL/TT	TT
Brand	Alliance
Tread pattern	324
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	13,72
Recommended rim size	5.50F
Maximum air pressure [bar].	3,80
Section width (mm)	189
Outer diameter of tyre [mm].	754
Stat. radius (SLR) [mm]	347
Rolling circumference [mm].	2250
Tread depth (mm)	12,0
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
105 A6	925	30		3,80	
101 A8	825	40		3,80	