

## **TYRES**

Product group	Tyres	
Item number	15222070	
Valid tyre size	7.00 - 18	
LI / SI / PR	123 A6 / 120 A8, 6 PR	
TL/TT	тт	
Brand	Alliance	
Tread pattern	324	



## Notes and features

- Agricultural bias tyre for use on tractors or as an implement tyre.
- Lugs at a 45° angle for high traction and good selfcleaning, even in the harshest operating conditions.
- The strong nylon casing ensures high operational safety and good traction transmission.



## **Technical Informations**

Item number	15222070
EAN	8903635004349
Valid tyre size	7.00 - 18
LI / SI / PR	123 A6 / 120 A8, 6 PR
TL/TT	тт
Brand	Alliance
Tread pattern	324
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	17,65
Recommended rim size	5.00F
Permitted rim size	5.50
Maximum air pressure [bar].	2,00
Section width (mm)	178
Outer diameter of tyre [mm].	803
Stat. radius (SLR) [mm]	373
Rolling circumference [mm].	2413
Guarantee period	7 years
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
123 A6	1550	30		2,00	
120 A8	1400	40		2,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.