

TYRES

Product group	Tyres
Item number	15222151
Valid tyre size	8.3 - 24
LI / SI / PR	105 A8, 8 PR
TL/TT	TT
Brand	Alliance
Tread pattern	324



Notes and features

- Agricultural bias tyre for use on tractors or as an implement tyre.
- Lugs at a 45° angle for high traction and good self-cleaning, even in the harshest operating conditions.
- The strong nylon casing ensures high operational safety and good traction transmission.

Technical Informations

Item number	15222151
EAN	8903635003144
Valid tyre size	8.3 - 24
LI / SI / PR	105 A8, 8 PR
TL/TT	TT
Brand	Alliance
Tread pattern	324
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	24,44
Recommended rim size	W7
Permitted rim size	W6
Maximum air pressure [bar].	3,10
Section width (mm)	211
Outer diameter of tyre [mm].	995
Stat. radius (SLR) [mm]	470
Rolling circumference [mm].	3020
Number of lugs	21x2
Lug width (mm)	20
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
105 A8	925	40		2,40	