Bohnenkamp Moving Professionals

20.09.2024

TYRES

Product group	Tyres
Item number	15222172
Valid tyre size	9.5 - 24
LI / SI / PR	112 A8, 8 PR
TL/TT	тт
Brand	Alliance
Tread pattern	FarmPRO 324





Notes and features

- The Alliance FarmPro 324 has a modern 45 degree lug • angle design, suitable for field and road applications.
- In field use, the tyre is characterised by very good • traction.
- The revised, new-look tread pattern provides excellent self-cleaning properties.
- Its particularly resistant rubber compound prevents the • enlargement of minor punctures.
- The complete R-1 range is available with this tread • pattern.

Bohnenkamp Moving Professionals

Technical Informations

Item number	15222172
EAN	8903635013891
Valid tyre size	9.5 - 24
LI / SI / PR	112 A8, 8 PR
TL/TT	тт
Brand	Alliance
Tread pattern	FarmPRO 324
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	26,53
Recommended rim size	W8
Permitted rim size	W7, W8H
Maximum air pressure [bar].	2,80
Section width (mm)	241
Outer diameter of tyre [mm].	1050
Stat. radius (SLR) [mm]	492
Rolling circumference [mm].	3128
Tread depth (mm)	31,0
Number of lugs	20x2
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
112 A8	1120	40		2,80	

20.09.2024

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.